

In the Claims

This listing of claims will replace all prior versions, and listings, of claims.

Listing of Claims

1. (Currently Amended) An apparatus for splitting a test piece,
comprising:

a base with a centerline;

two pillars disposed on the base separated by a fixed first interval to support the
test piece at a first side thereof, wherein a connection line between the
pillars is perpendicular to and divided equally by the centerline; and

a sliding piece disposed on the base at a second side of the test piece, which is
opposite to the first side thereof ~~slidable along the centerline~~, wherein the
sliding piece is slidable along the centerline and has two fingers parallel to
the centerline separated by a second interval, which is smaller than the
first interval, and a connection line between the tips of the fingers is
perpendicular to and divided equally by the centerline.
2. (Original) The apparatus as claimed in claim 1, wherein the base
has two pivot points at the both sides of the centerline to install the pillars.
3. (Original) The apparatus as claimed in claim 2, wherein the pivot
points are separated by the first interval, which is divided equally by the
centerline.

4. (Original) The apparatus as claimed in claim 1, wherein the base has a straight groove along the centerline, and the sliding piece has a protrusion movable in the groove along the centerline.

5. (Original) An operating method for the apparatus as claimed in claim 1, comprising the step of:

providing a test piece having a working surface with a target point;
forming two slits separated apart on the working surface and aligned with the target point in a predetermined line;
fixing the test piece on the base with the working surface contacting the pillars and the slits aligned with the centerline of the base;
moving the sliding piece, such that the fingers contacts the test piece; and
pushing the sliding piece to split the test piece along the predetermined line by the fingers of the sliding piece and the pillars.

6. (New) The apparatus as claimed in claim 1, wherein the base has a straight groove along the centerline, the sliding piece has a protrusion movable in the groove along the centerline, and the width of the protrusion substantially matches the width of the groove on the base, such that the sliding piece is movable in the groove along the centerline.

7. (New) An apparatus for splitting a test piece, comprising:
a base having a groove formed along a centerline defined on the base;

two pillars disposed on the base and separated by a fixed first interval to support the test piece, wherein a connection line between the pillars is perpendicular to and divided equally by the centerline; and

a sliding piece, disposed on the base, having a protrusion slidable in the groove, wherein the sliding piece has two fingers parallel to the centerline and separated by a second interval, which is smaller than the first interval, and a connection line between the tips of the fingers is perpendicular to and divided equally by the centerline.